

DERCOLYTE A 125

DERCOLYTE A 125 is produced from the polymerisation of alpha pinene. It is a tackifying resin recommended to improve the adhesive properties (tack, adhesion, heat resistance) of Hot Melt based or solvent based adhesives.

TYPICAL VALUES

Softening point, Ring and Ball, °C	125
Gardner colour, 50 resin / 50 toluene	3

DRT analytical methods are available on request

OTHER TECHNICAL DATA

Glass temperature (Tg), °C	80
Molecular weight (Mw), g/mole	900
Soluble in aromatic, aliphatic and chlorinated solvents	
Insoluble in alcohol and ketones	

USES

Hot Melt Pressure Sensitive Adhesives based on SIS or SBS

Solvent based Adhesives

IDENTIFIERS

EINECS	Polymer. All monomers are listed
--------	----------------------------------

TRANSPORT

HANDLING & STORAGE	Under cover and at temperatures below 30°C
STABILITY	About 6 months storage conditions and inventory control must be observed.
PACKAGING	Flaked in 25 kg net weight paper bags on wrapped pallets of 750 kg net weight.
CUSTOMS TARIFF	3911100090

TECHNICAL DATA SHEET / 08.08.11

The data herein are based on our knowledge about above product. They are without conditions or warranties, expressed or implied regarding the uses of the product.

LES DÉRIVÉS RÉSINIQUES & TERPÉNIQUES

30 rue Gambetta - BP 206 - 40105 DAX Cedex - France
www.drtr.fr - Tel. : +33 (0)5 58 56 62 00 - Fax : +33 (0)5 58 56 62 40

